


Terminal cónico cerrado Ropeblock CSS



Información del producto



Marcado: According to standard, CE-marked

Certificación: EN 10204

Referencia CYE	Rope diameter mm	Fuerza mínima de rotura MBL	Finish	Strand Ø mm	TL mm	TA mm	A mm	B mm	C mm	Ø H mm	K	T	Peso kg
Y6ATECSS296G	6-7	8	Galvanized	-	101	37	50	40	11	9,1	22	13	0,3
Y6ATECSS297G	8-10	12	Galvanized	-	119	43	57	48	14	12,6	25	18	0,5
Y6ATECSS298G	11-13	20	Galvanized	-	140	51	64	59	17,5	14,6	30	23	0,7
Y6ATECSS299G	14-16	25	Galvanized	13	162	67	76	65	21	18,1	36	26	1,4
Y6ATECSS200G	18-19	40	Galvanized	14-16	194	76	89	78	27	21,9	42	32	2,2
Y6ATECSS201G	20-22	55	Galvanized	18-19	224	92	101	90	33	24,9	47	38	3,8
Y6ATECSS204y	23-26	75	Galvanized	20-22	253	104	114	103	36	28,8	57	44	5,4

Y6ATECSS204y	23-26	75	Painted	20-22	253	104	114	103	36	28,8	57	44	5,4
Y6ATECSS207y	27-30	90	Painted	23-26	282	114	127	116	39	32,9	65	51	7
Y6ATECSS207y	27-30	90	Galvanized	23-26	282	114	127	116	39	32,9	65	51	7
Y6ATECSS212y	31-36	125	Galvanized	27-28	312	126	139	130	43	39,2	71	57	10
Y6ATECSS212y	31-36	125	Painted	27-28	312	126	139	130	43	39,2	71	57	10
Y6ATECSS215y	37-39	150	Painted	30-32	358	136	152	155	51	42,5	81	63	13
Y6ATECSS215y	37-39	150	Galvanized	30-32	358	136	152	155	51	42,5	81	63	13
Y6ATECSS217y	40-42	170	Painted	33-35	390	146	165	171	54	45,5	83	70	17
Y6ATECSS217y	40-42	170	Galvanized	33-35	390	146	165	171	54	45,5	83	70	17
Y6ATECSS219y	43-48	225	Painted	36-40	443	171	190	198	55	52,5	93	76	26
Y6ATECSS219y	43-48	225	Galvanized	36-40	443	171	190	198	55	52,5	93	76	26
Y6ATECSS222y	49-54	280	Galvanized	42-45	502	193	216	224	62	59,1	100	82	37
Y6ATECSS222y	49-54	280	Painted	42-45	502	193	216	224	62	59,1	100	82	37
Y6ATECSS224y	55-60	360	Painted	46-48	548	216	228	247	73	65,1	112	92	50
Y6ATECSS224y	55-60	360	Galvanized	46-48	548	216	228	247	73	65,1	112	92	50
Y6ATECSS226y	61-68	425	Painted	50-54	257	241	248	270	79	73,4	140	102	66
Y6ATECSS226y	61-68	425	Galvanized	50-54	257	241	248	270	79	73,4	140	102	66
Y6ATECSS227y	69-75	460	Painted	56-62	644	273	279	286	79	79,4	159	124	91
Y6ATECSS227y	69-75	460	Galvanized	56-62	644	273	279	286	79	79,4	159	124	91
Y6ATECSS228y	76-80	560	Painted	64-67	696	292	315	298	83	88,2	171	133	117
Y6ATECSS228y	76-80	560	Galvanized	64-67	696	292	315	298	83	88,2	171	133	117
Y6ATECSS229y	81-86	625	Galvanized	69-76	743	311	330	311	102	92,4	184	146	125
Y6ATECSS229y	81-86	625	Painted	69-76	743	311	330	311	102	92,4	184	146	125

Y6ATECSS230y	87-93	720	Galvanized	78-86	788	330	356	330	102	98,8	197	159	176
Y6ATECSS230y	87-93	720	Painted	78-86	788	330	356	330	102	98,8	197	159	176
Y6ATECSS231y	94-102	875	Galvanized	88-96	845	362	381	356	108	107,8	216	178	228
Y6ATECSS231y	94-102	875	Painted	88-96	845	362	381	356	108	107,8	216	178	228
Y6ATECSS233y	108-115	1.200	Painted	98-110	1.000	405	450	425	125	129,5	235	190	323
Y6ATECSS233y	108-115	1.200	Galvanized	98-110	1.000	405	450	425	125	129,5	235	190	323
Y6ATECSS240y	120-130	1.400	Painted	112-124	1.150	450	500	525	125	147,1	260	200	447
Y6ATECSS240y	120-130	1.400	Galvanized	112-124	1.150	450	500	525	125	147,1	260	200	447
Y6ATECSS245y	135-140	1.600	Galvanized	125-132	1.185	520	540	495	150	153,9	290	220	645
Y6ATECSS245y	135-140	1.600	Painted	125-132	1.185	520	540	495	150	153,9	290	220	645
Y6ATECSS250y	142-153	2.000	Galvanized	133-143	1.285	545	585	530	170	171,1	305	240	741
Y6ATECSS250y	142-153	2.000	Painted	133-143	1.285	545	585	530	170	171,1	305	240	741
Y6ATECSS255y	154-165	2.220	Painted	144-154	1.370	575	630	565	175	185,1	330	250	860
Y6ATECSS255y	154-165	2.220	Galvanized	144-154	1.370	575	630	565	175	185,1	330	250	860
Y6ATECSS260y	166-178	2.500	Painted	155-166	1.450	595	680	590	180	199,1	330	270	985
Y6ATECSS260y	166-178	2.500	Galvanized	155-166	1.450	595	680	590	180	199,1	330	270	985
Y6ATECSS265y	180-191	2.800	Painted	167-179	1.535	625	725	620	190	213	350	290	1.183
Y6ATECSS265y	180-191	2.800	Galvanized	167-179	1.535	625	725	620	190	213	350	290	1.183
Y6ATECSS270y	192-204	3.200	Galvanized	180-191	1.635	690	775	650	210	228,5	395	305	1.487
Y6ATECSS270y	192-204	3.200	Painted	180-191	1.635	690	775	650	210	228,5	395	305	1.487

Blueprint

